

TYRES

Product group	Tyres
Item number	15727464
Valid tyre size	270 / 80 R 36
LI / SI / PR	134 A8 / 134 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 955



Notes and features

- Row crop tyre for use on tractors as well as self-propelled and towed field sprayers
- Also offers good ride comfort on the road
- Rounded shoulders provide protection against plant and ground damage
- High load capacity also enables use with heavy attachments
- Offers high machine stability and very good ride comfort, approved up to 50 km/h

Technical Informations

Item number	15727464
EAN	8903094067046
Valid tyre size	270 / 80 R 36
LI / SI / PR	134 A8 / 134 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 955
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	55,90
Recommended rim size	W9
Permitted rim size	W8, W10
Maximum air pressure [bar].	4,00
Section width (mm)	275
Outer diameter of tyre [mm].	1346
Stat. radius (SLR) [mm]	629
Rolling circumference [mm].	4090
Tread depth (mm)	34,5
Number of lugs	23x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
134 A8	2120	50		4,00	
134 B	2120	40		4,00	