

TYRES

Product group	Tyres	
Item number	15727465	
Valid tyre size	270 / 95 R 36	
LI / SI / PR	139 A8 / 139 B	
TL/TT	TL	
Brand	BKT	
Tread pattern	Agrimax RT 955	





Notes and features

- Row crop tyre for use on tractors as well as self-propelled and towed field sprayers
- Also offers good ride comfort on the road
- Rounded shoulders provide protection against plant and ground damage
- High load capacity also enables use with heavy attachments
- Offers high machine stability and very good ride comfort, approved up to 50 km/h



Technical Informations

Item number	15727465
EAN	8903094027484
Valid tyre size	270 / 95 R 36
Alternative size 1	11.2R36
LI / SI / PR	139 A8 / 139 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 955
Antistatic	No .
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	60,54
Recommended rim size	W9
Permitted rim size	W8, W10
Maximum air pressure [bar].	4,00
Section width (mm)	275
Outer diameter of tyre [mm].	1428
Stat. radius (SLR) [mm]	665
Rolling circumference [mm].	4368
Tread depth (mm)	35,0
Number of lugs	25x2
Lug width (mm)	27
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
139 A8	2430	40		4,00	
139 B	2430	50		4,00	