

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 15727485 |
| Valid tyre size | 300 / 85 R 42 |
| LI / SI / PR | 144 A8 / 144 B |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax RT 955 |



Notes and features

- Row crop tyre for use on tractors as well as self-propelled and towed field sprayers
- Also offers good ride comfort on the road
- Rounded shoulders provide protection against plant and ground damage
- High load capacity also enables use with heavy attachments
- Offers high machine stability and very good ride comfort, approved up to 50 km/h

Technical Informations

| | |
|------------------------------|----------------|
| Item number | 15727485 |
| EAN | 8903094040636 |
| Valid tyre size | 300 / 85 R 42 |
| Alternative size 1 | 11.2R42 |
| LI / SI / PR | 144 A8 / 144 B |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax RT 955 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 72,27 |
| Recommended rim size | W9 |
| Permitted rim size | W10, W11 |
| Maximum air pressure [bar]. | 4,00 |
| Section width (mm) | 295 |
| Outer diameter of tyre [mm]. | 1577 |
| Stat. radius (SLR) [mm] | 745 |
| Rolling circumference [mm]. | 4850 |
| Tread depth (mm) | 36,0 |
| Number of lugs | 26x2 |
| Tyre capacity 75% [ltr.] | 190.9 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 144 A8 | 2800 | 40 | | 4,00 | |
| 144 B | 2800 | 50 | | 4,00 | |