

TYRES

Product group	Tyres
Item number	15727490
Valid tyre size	320 / 90 R 42
LI / SI / PR	139 A8 / 139 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 945



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Row crop tyre for use on tractors as well as self-propelled and towed field sprayers
- Also offers good ride comfort on the road
- Rounded shoulders provide protection against plant and ground damage
- High load capacity also enables use with heavy attachments
- Offers high machine stability and very good ride comfort, approved up to 50 km/h

Technical Informations

Item number	15727490
EAN	8903094038664
Valid tyre size	320 / 90 R 42
Alternative size 1	12.4R42
LI / SI / PR	139 A8 / 139 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 945
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	98,27
Recommended rim size	W10
Permitted rim size	W9, W11
Maximum air pressure [bar].	2,40
Section width (mm)	319
Outer diameter of tyre [mm].	1643
Stat. radius (SLR) [mm]	760
Rolling circumference [mm].	4944
Tread depth (mm)	43,0
Number of lugs	30x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
139 A8	2430	40		2,40	
139 B	2430	50		2,40	