

## TYRES

Product group	Tyres
Item number	15727510
Valid tyre size	270 / 95 R 44
LI / SI / PR	142 A8 / 142 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 955



## Notes and features

- Row crop tyre for use on tractors as well as self-propelled and towed field sprayers
- Also offers good ride comfort on the road
- Rounded shoulders provide protection against plant and ground damage
- High load capacity also enables use with heavy attachments
- Offers high machine stability and very good ride comfort, approved up to 50 km/h

## Technical Informations

Item number	15727510
EAN	8903094028146
Valid tyre size	270 / 95 R 44
Alternative size 1	11.2R44
LI / SI / PR	142 A8 / 142 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 955
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	71,66
Recommended rim size	W9
Permitted rim size	W8, W10
Maximum air pressure [bar].	4,00
Section width (mm)	275
Outer diameter of tyre [mm].	1632
Stat. radius (SLR) [mm]	764
Rolling circumference [mm].	4983
Tread depth (mm)	35,0
Number of lugs	28x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
142 A8	2650	40		4,00	
142 B	2650	50		4,00	