

TYRES

Product group	Tyres
Item number	15727571
Valid tyre size	320 / 90 R 46
LI / SI / PR	151 A8 / 148 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 945



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Row crop tyre for use on tractors as well as self-propelled and towed field sprayers
- Also offers good ride comfort on the road
- Rounded shoulders provide protection against plant and ground damage
- High load capacity also enables use with heavy attachments
- Offers high machine stability and very good ride comfort, approved up to 50 km/h

Technical Informations

Item number	15727571
EAN	8903094051694
Valid tyre size	320 / 90 R 46
Alternative size 1	12.4R46
LI / SI / PR	151 A8 / 148 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 945
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	108,68
Recommended rim size	10
Permitted rim size	9, 11
Maximum air pressure [bar].	3,60
Section width (mm)	319
Outer diameter of tyre [mm].	1744
Stat. radius (SLR) [mm]	810
Rolling circumference [mm].	5232
Tread depth (mm)	42,5
Number of lugs	32x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 A8	3450	40		3,60	
148 D	3150	65		3,60	