## Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	15727586
Valid tyre size	340 / 85 R 46
LI / SI / PR	150 A8 / 150 B
TL/TT	TL
Brand	ВКТ
Tread pattern	Agrimax RT 955



Notes and features

- Row crop tyre for use on tractors as well as self-propelled and towed field sprayers
- Also offers good ride comfort on the road
- Rounded shoulders provide protection against plant and ground damage
- High load capacity also enables use with heavy attachments
- Offers high machine stability and very good ride comfort, approved up to 50 km/h

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

## **Technical Informations**

Item number	15727586
EAN	8903094044726
Valid tyre size	340 / 85 R 46
Alternative size 1	13.6R46
LI / SI / PR	150 A8 / 150 B
TL/TT	TL
Brand	ВКТ
Tread pattern	Agrimax RT 955
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	101,10
Recommended rim size	W12
Permitted rim size	W11, W10
Maximum air pressure [bar].	3,60
Section width (mm)	353
Outer diameter of tyre [mm].	1746
Stat. radius (SLR) [mm]	826
Rolling circumference [mm].	5346
Tread depth (mm)	36,5
Number of lugs	28x2
Lug width (mm)	32
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
150 A8	3350	40		3,60	
150 B	3350	50		3,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.