

## TYRES

|                 |                |
|-----------------|----------------|
| Product group   | Tyres          |
| Item number     | 15727600       |
| Valid tyre size | 270 / 95 R 48  |
| LI / SI / PR    | 144 A8 / 144 B |
| TL/TT           | TL             |
| Brand           | BKT            |
| Tread pattern   | Agrimax RT 955 |



## Notes and features

- Row crop tyre for use on tractors as well as self-propelled and towed field sprayers
- Also offers good ride comfort on the road
- Rounded shoulders provide protection against plant and ground damage
- High load capacity also enables use with heavy attachments
- Offers high machine stability and very good ride comfort, approved up to 50 km/h

## Technical Informations

|                              |                |
|------------------------------|----------------|
| Item number                  | 15727600       |
| EAN                          | 8903094021840  |
| Valid tyre size              | 270 / 95 R 48  |
| Alternative size 1           | 11.2R48        |
| LI / SI / PR                 | 144 A8 / 144 B |
| TL/TT                        | TL             |
| Brand                        | BKT            |
| Tread pattern                | Agrimax RT 955 |
| Antistatic                   | No             |
| Tyre colour                  | Black          |
| ECE regulation number        | ECE 106        |
| Nettogewicht [kg] (gültig)   | 77,58          |
| Recommended rim size         | W9             |
| Permitted rim size           | W8, W10        |
| Maximum air pressure [bar].  | 4,00           |
| Section width (mm)           | 275            |
| Outer diameter of tyre [mm]. | 1733           |
| Stat. radius (SLR) [mm]      | 820            |
| Rolling circumference [mm].  | 5351           |
| Tread depth (mm)             | 35,0           |
| Number of lugs               | 30x2           |
| Lug width (mm)               | 27             |
| E-Ready                      | No             |

## Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 144 A8 | 2800               | 40           |               | 4,00                     |              |
| 144 B  | 2800               | 50           |               | 4,00                     |              |