

TYRES

Product group	Tyres
Item number	15727630
Valid tyre size	320 / 90 R 50
LI / SI / PR	150 A8 / 150 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 945



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Row crop tyre for use on tractors as well as self-propelled and towed field sprayers
- Also offers good ride comfort on the road
- Rounded shoulders provide protection against plant and ground damage
- High load capacity also enables use with heavy attachments
- Offers high machine stability and very good ride comfort, approved up to 50 km/h

Technical Informations

Item number	15727630
EAN	8903094037612
Valid tyre size	320 / 90 R 50
Alternative size 1	12.4R50
LI / SI / PR	150 A8 / 150 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 945
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	114,46
Recommended rim size	W10
Permitted rim size	W9, W11
Maximum air pressure [bar].	3,60
Section width (mm)	319
Outer diameter of tyre [mm].	1846
Stat. radius (SLR) [mm]	873
Rolling circumference [mm].	5618
Tread depth (mm)	43,0
Number of lugs	34x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
150 A8	3350	40		3,60	
150 B	3350	50		3,60	