# Bohnenkamp Moving Professionals

**TYRES** 

Product group	Tyres
Item number	15727643
Valid tyre size	VF 380 / 90 R 50
LI / SI / PR	175 D
TL/TT	TL
Brand	ВКТ
Tread pattern	Agrimax Spargo



#### Notes and features

- Row crop tyre with VF technology for self-propelled and towed field sprayers and tractors.
- Up to 40% higher load capacity at constant inflation pressure or up to 40% lower inflation pressure with the same payload compared with standard tyres
- Excellent plant and soil protection allows yield increases.
- Excellent ride comfort and high machine stability.

# Bohnenkamp Moving Professionals

#### **Technical Informations**

Item number	15727643
EAN	8903094065264
Valid tyre size	VF 380 / 90 R 50
LI / SI / PR	175 D
TL/TT	TL
Brand	ВКТ
Tread pattern	Agrimax Spargo
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	174,50
Recommended rim size	W13B
Permitted rim size	W12B
Maximum air pressure [bar].	4,40
Section width (mm)	390
Tread width (mm)	326
Outer diameter of tyre [mm].	1950
Stat. radius (SLR) [mm]	893
Rolling circumference [mm].	5950
Tread depth (mm)	34,5
Number of lugs	34x2
E-Ready	No

### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
175 D	6900	65		4,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.