

TYRES

| | |
|-----------------|-------------------|
| Product group | Tyres |
| Item number | 15727645 |
| Valid tyre size | VF 380 / 105 R 50 |
| LI / SI / PR | 179 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax Spargo |



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Row crop tyre with VF technology for self-propelled and towed field sprayers and tractors.
- Up to 40% higher load capacity at constant inflation pressure or up to 40% lower inflation pressure with the same payload compared with standard tyres
- Excellent plant and soil protection allows yield increases.
- Excellent ride comfort and high machine stability.

Technical Informations

| | |
|------------------------------|-------------------|
| Item number | 15727645 |
| EAN | 8903094048113 |
| Valid tyre size | VF 380 / 105 R 50 |
| LI / SI / PR | 179 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax Spargo |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 206,90 |
| Recommended rim size | DW13 |
| Permitted rim size | TW13, W13, W12 |
| Maximum air pressure [bar]. | 4,40 |
| Section width (mm) | 400 |
| Tread width (mm) | 345 |
| Outer diameter of tyre [mm]. | 2050 |
| Stat. radius (SLR) [mm] | 934 |
| Speed Radius Index (SRI) | 975 |
| Rolling circumference [mm]. | 6211 |
| Tread depth (mm) | 46,0 |
| Number of lugs | 36x2 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 179 D | 7750 | 65 | | 4,40 | |