

TYRES

| | |
|-----------------|------------------|
| Product group | Tyres |
| Item number | 15727655 |
| Valid tyre size | VF 420 / 95 R 50 |
| LI / SI / PR | 177 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax Spargo |



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Row crop tyre with VF technology for self-propelled and towed field sprayers and tractors.
- Up to 40% higher load capacity at constant inflation pressure or up to 40% lower inflation pressure with the same payload compared with standard tyres
- Excellent plant and soil protection allows yield increases.
- Excellent ride comfort and high machine stability.

Technical Informations

| | |
|------------------------------|------------------|
| Item number | 15727655 |
| EAN | 8903094051380 |
| Valid tyre size | VF 420 / 95 R 50 |
| LI / SI / PR | 177 D |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Agrimax Spargo |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 212,60 |
| Recommended rim size | DW14 |
| Permitted rim size | DW13, W13, W14 |
| Maximum air pressure [bar]. | 3,60 |
| Section width (mm) | 419 |
| Tread width (mm) | 360 |
| Outer diameter of tyre [mm]. | 2068 |
| Stat. radius (SLR) [mm] | 943 |
| Speed Radius Index (SRI) | 975 |
| Rolling circumference [mm]. | 6210 |
| Tread depth (mm) | 46,0 |
| Number of lugs | 33x2 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 177 D | 7300 | 65 | | 3,60 | |