

TYRES

Product group	Tyres
Item number	15727700
Valid tyre size	300 / 95 R 52
LI / SI / PR	151 A8 / 151 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 955



Notes and features

- Row crop tyre for use on tractors as well as self-propelled and towed field sprayers
- Also offers good ride comfort on the road
- Rounded shoulders provide protection against plant and ground damage
- High load capacity also enables use with heavy attachments
- Offers high machine stability and very good ride comfort, approved up to 50 km/h

Technical Informations

Item number	15727700
EAN	8903094029747
Valid tyre size	300 / 95 R 52
Alternative size 1	12.4R52
LI / SI / PR	151 A8 / 151 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 955
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	95,80
Recommended rim size	W9
Permitted rim size	W10, W11, DW10, DW11
Maximum air pressure [bar].	4,00
Section width (mm)	295
Outer diameter of tyre [mm].	1891
Stat. radius (SLR) [mm]	889
Rolling circumference [mm].	5774
Tread depth (mm)	36,0
Number of lugs	30x2
Tyre capacity 75% [ltr.]	224
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 A8	3450	40		4,00	
151 B	3450	50		4,00	