

TYRES

Product group	Tyres
Item number	15727720
Valid tyre size	270 / 95 R 54
LI / SI / PR	146 A8 / 146 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 955





Notes and features

- Row crop tyre for use on tractors as well as self-propelled and towed field sprayers
- Also offers good ride comfort on the road
- Rounded shoulders provide protection against plant and ground damage
- High load capacity also enables use with heavy attachments
- Offers high machine stability and very good ride comfort, approved up to 50 km/h



Technical Informations

Item number	15727720
EAN	8903094032839
Valid tyre size	270 / 95 R 54
Alternative size 1	11.2R54
LI / SI / PR	146 A8 / 146 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 955
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	91,50
Recommended rim size	W9
Permitted rim size	W8, W10
Maximum air pressure [bar].	4,00
Section width (mm)	275
Outer diameter of tyre [mm].	1885
Stat. radius (SLR) [mm]	894
Rolling circumference [mm].	5815
Tread depth (mm)	35,0
Number of lugs	33x2
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
146 A8	3000	40		4,00	
146 B	3000	50		4,00	