

TYRES

Product group	Tyres
Item number	15727755
Valid tyre size	900 / 60 R 32
LI / SI / PR	181 A8 / 178 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 600



Notes and features

- The RT 600 is specially designed for grassland use and sensitive soils.
- Ideal for forage harvesters for green forage harvesting.
- Rounded shoulders and reduced tread depth protect the turf.
- Large footprint enables excellent flotation properties.
- Reinforced bead provides high load capacity.

Technical Informations

Item number	15727755
EAN	8903094062423
Valid tyre size	900 / 60 R 32
LI / SI / PR	181 A8 / 178 B
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 600
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	338,00
Recommended rim size	DW27B
Permitted rim size	DW28B, DW30B
Maximum air pressure [bar].	3,20
Section width (mm)	896
Tread width (mm)	835
Outer diameter of tyre [mm].	1893
Stat. radius (SLR) [mm]	841
Rolling circumference [mm].	5697
Tread depth (mm)	46,5
Number of lugs	21x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
181 A8	8250	40		3,20	
178 B	7500	50		3,20	