

TYRES

Product group	Tyres
Item number	15727850
Valid tyre size	500 / 80 R 28
LI / SI / PR	164 A8 / 176 A8
TL/TT	TL
Brand	BKT
Tread pattern	RM 500



Bohnenkamp
Moving Professionals



Notes and features

- The BKT RM 500 is a radial tyre for harvesting machines.
- The strong, steel belt casing and the special tread pattern design provide high loading capacities and excellent cut and tear resistance.
- Due to its large contact area, the ground pressure is optimally distributed and soil compaction minimised.

Technical Informations

Item number	15727850
EAN	8903094063697
Valid tyre size	500 / 80 R 28
LI / SI / PR	164 A8 / 176 A8
TL/TT	TL
Brand	BKT
Tread pattern	RM 500
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	151,00
Recommended rim size	W16L
Permitted rim size	W15L
Maximum air pressure [bar].	3,20
Section width (mm)	503
Outer diameter of tyre [mm].	1495
Stat. radius (SLR) [mm]	635
Speed Radius Index (SRI)	700
Rolling circumference [mm].	4355
Tread depth (mm)	38,0
Number of lugs	21x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 A8	5000	40	Drive Wheel	3,20	
176 A8	7100	40	Free Rolling	3,20	