

## TYRES

|                 |                       |
|-----------------|-----------------------|
| Product group   | Tyres                 |
| Item number     | 15731050              |
| Valid tyre size | 10.5 - 18             |
| LI / SI / PR    | 131 A8 / 130 B, 10 PR |
| TL/TT           | TL                    |
| Brand           | BKT                   |
| Tread pattern   | MP 600                |



Bohnenkamp  
Moving Professionals

**BKT**  
GROWING TOGETHER

## Notes and features

- The MP 600 is a versatile multi purpose tyre for various uses.
- It is suitable for operations with a large share of road journeys but also as an agro-industrial tyre, for example on skid steer loaders and telescopic handlers.
- The wide tread pattern provides for good traction on any surface and for an exceptional level of stability.
- The lug design features very good self-cleaning properties.
- Owing to its sturdy carcass, the tyre is characterised by a high level of durability and a long service life.

## Technical Informations

|                              |                       |
|------------------------------|-----------------------|
| Item number                  | 15731050              |
| EAN                          | 8903094015290         |
| Valid tyre size              | 10.5 - 18             |
| LI / SI / PR                 | 131 A8 / 130 B, 10 PR |
| TL/TT                        | TL                    |
| Brand                        | BKT                   |
| Tread pattern                | MP 600                |
| Antistatic                   | No                    |
| Tyre colour                  | Black                 |
| ECE regulation number        | ECE 106               |
| Nettogewicht [kg] (gültig)   | 29,10                 |
| Recommended rim size         | 9                     |
| Permitted rim size           | 9SDC                  |
| Maximum air pressure [bar].  | 3,75                  |
| Section width (mm)           | 272                   |
| Outer diameter of tyre [mm]. | 920                   |
| Stat. radius (SLR) [mm]      | 420                   |
| Rolling circumference [mm].  | 2740                  |
| Tread depth (mm)             | 22,0                  |
| Number of lugs               | 20x2                  |
| E-Ready                      | No                    |

## Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 131 A8 | 1950               | 40           |               | 3,75                     |              |
| 130 B  | 1900               | 50           |               | 3,75                     |              |