

TYRES

Product group	Tyres
Item number	15731061
Valid tyre size	12.5 - 18
LI / SI / PR	130 F, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	MP 570



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT MP 570 was developed for road construction and excavation work.
- The tyre features excellent traction and good self-cleaning properties.
- Designed for sandy, loose surfaces.

Technical Informations

Item number	15731061
EAN	8903094038312
Valid tyre size	12.5 - 18
LI / SI / PR	130 F, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	MP 570
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	43,25
Recommended rim size	11
Permitted rim size	12SDC
Maximum air pressure [bar].	3,00
Section width (mm)	308
Outer diameter of tyre [mm].	990
Stat. radius (SLR) [mm]	450
Rolling circumference [mm].	2950
Tread depth (mm)	24,0
Number of lugs	22x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
130 F	1900	80		3,00	