

TYRES

Product group	Tyres
Item number	15731067
Valid tyre size	12.5 - 18
LI / SI / PR	136 B, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	MP 600



Bohnenkamp
Moving Professionals



Notes and features

- The MP 600 is a versatile multi purpose tyre for various uses.
- It is suitable for operations with a large share of road journeys but also as an agro-industrial tyre, for example on skid steer loaders and telescopic handlers.
- The wide tread pattern provides for good traction on any surface and for an exceptional level of stability.
- The lug design features very good self-cleaning properties.
- Owing to its sturdy carcass, the tyre is characterised by a high level of durability and a long service life.

Technical Informations

Item number	15731067
EAN	8903094015313
Valid tyre size	12.5 - 18
LI / SI / PR	136 B, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	MP 600
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	44,76
Recommended rim size	11
Permitted rim size	12SDC
Maximum air pressure [bar].	3,50
Section width (mm)	308
Outer diameter of tyre [mm].	990
Stat. radius (SLR) [mm]	450
Rolling circumference [mm].	2950
Tread depth (mm)	24,0
Number of lugs	21x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
136 B	2240	50		3,50	
	2300	40		3,50	