

TYRES

Product group	Tyres
Item number	15731073
Valid tyre size	12.5 - 18
LI / SI / PR	128 G, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	MP 567



Bohnenkamp
■ ■ ■ Moving Professionals



Notes and features

- The BKT MP 567 is a multi purpose tyre offering maximum flexibility.
- The tyre features good traction in all weathers.
- Suitable for on- and off-road use.
- The open tread pattern allows for efficient self-cleaning.
- Suitable for use on vehicles such as Unimogs, backhoe loaders, dumpers, etc.

Technical Informations

Item number	15731073
EAN	8903094038107
Valid tyre size	12.5 - 18
LI / SI / PR	128 G, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	MP 567
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	43,62
Recommended rim size	11
Permitted rim size	12SDC
Maximum air pressure [bar].	3,00
Section width (mm)	325
Outer diameter of tyre [mm].	990
Stat. radius (SLR) [mm]	450
Rolling circumference [mm].	2940
Tread depth (mm)	22,0
Number of lugs	21x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
128 G	1800	90		3,00	