

## TYRES

Product group	Tyres
Item number	15731088
Valid tyre size	6.50 - 20
LI / SI / PR	106 A6, 10 PR
TL/TT	TT
Brand	BKT
Tread pattern	MP 585



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- The BKT MP 585 delivers good performance on hard surfaces.
- The shoulder lugs provide good traction in the field.
- Suitable for use on various utility vehicles and for various applications.

## Technical Informations

Item number	15731088
EAN	8903094051243
Valid tyre size	6.50 - 20
LI / SI / PR	106 A6, 10 PR
TL/TT	TT
Brand	BKT
Tread pattern	MP 585
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	15,94
Recommended rim size	5.50F
Permitted rim size	4.00E, 5.00F
Maximum air pressure [bar].	5,50
Section width (mm)	200
Outer diameter of tyre [mm].	875
Stat. radius (SLR) [mm]	410
Rolling circumference [mm].	2600
Tread depth (mm)	15,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
106 A6	950	30		5,50	