

TYRES

Product group	Tyres	
Item number	15731092	
Valid tyre size	10.5 - 20	
LI / SI / PR	128 G, 10 PR	
TL/TT	TL	
Brand	BKT	
Tread pattern	MP 567	





Notes and features

- The BKT MP 567 is a multi purpose tyre offering maximum flexibility.
- The tyre features good traction in all weathers.
- Suitable for on- and off-road use.

- The open tread pattern allows for efficient self-cleaning.
- Suitable for use on vehicles such as Unimogs, backhoe loaders, dumpers, etc.



Technical Informations

Item number	15731092
EAN	8903094038091
Valid tyre size	10.5 - 20
LI / SI / PR	128 G, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	MP 567
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	36,61
Recommended rim size	9
Permitted rim size	9SDC
Maximum air pressure [bar].	3,75
Section width (mm)	270
Outer diameter of tyre [mm].	955
Stat. radius (SLR) [mm]	445
Rolling circumference [mm].	2880
Tread depth (mm)	22,0
Number of lugs	22x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
128 G	1800	90		3,75	
	2070	40		3,75	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.