Bohnenkamp Moving Professionals

16.11.2024

TYRES

Product group	Tyres	
Item number	15731121	
Valid tyre size	12.5 - 20	
LI / SI / PR	133 F, 12 PR	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	MP 570	





Notes and features

- The BKT MP 570 was developed for road construction and excavation work.
- The tyre features excellent traction and good self-cleaning properties.
- Designed for sandy, loose surfaces.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15731121
EAN	8903094038329
Valid tyre size	12.5 - 20
LI / SI / PR	133 F, 12 PR
TL/TT	TL
Brand	ВКТ
Tread pattern	MP 570
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	49,70
Recommended rim size	11
Permitted rim size	12SDC
Maximum air pressure [bar].	3,50
Section width (mm)	335
Outer diameter of tyre [mm].	1050
Stat. radius (SLR) [mm]	480
Rolling circumference [mm].	3130
Tread depth (mm)	22,0
Number of lugs	23x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
133 F	2060	80		3,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.