

TYRES

| | |
|-----------------|--------------|
| Product group | Tyres |
| Item number | 15731126 |
| Valid tyre size | 12.5 - 20 |
| LI / SI / PR | 132 G, 12 PR |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | MP 585 |



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT MP 585 delivers good performance on hard surfaces.
- The shoulder lugs provide good traction in the field.
- Suitable for use on various utility vehicles and for various applications.

Technical Informations

| | |
|------------------------------|---------------|
| Item number | 15731126 |
| EAN | 8903094038404 |
| Valid tyre size | 12.5 - 20 |
| LI / SI / PR | 132 G, 12 PR |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | MP 585 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54 |
| Nettogewicht [kg] (gültig) | 46,97 |
| Recommended rim size | 11 |
| Permitted rim size | 12SDC |
| Maximum air pressure [bar]. | 3,50 |
| Section width (mm) | 335 |
| Outer diameter of tyre [mm]. | 1050 |
| Stat. radius (SLR) [mm] | 480 |
| Rolling circumference [mm]. | 3130 |
| Tread depth (mm) | 19,0 |
| Number of lugs | 25x2 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 132 G | 2000 | 90 | | 3,50 | |