

TYRES

Product group	Tyres
Item number	15731136
Valid tyre size	14.5 - 20
LI / SI / PR	148 A8 / 143 G, 18 PR
TL/TT	TL
Brand	BKT
Tread pattern	MP 567



Bohnenkamp
■ ■ ■ Moving Professionals



Notes and features

- The BKT MP 567 is a multi purpose tyre offering maximum flexibility.
- The tyre features good traction in all weathers.
- Suitable for on- and off-road use.
- The open tread pattern allows for efficient self-cleaning.
- Suitable for use on vehicles such as Unimogs, backhoe loaders, dumpers, etc.

Technical Informations

Item number	15731136
EAN	8903094038381
Valid tyre size	14.5 - 20
LI / SI / PR	148 A8 / 143 G, 18 PR
TL/TT	TL
Brand	BKT
Tread pattern	MP 567
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	60,72
Recommended rim size	11
Permitted rim size	12SDC
Maximum air pressure [bar].	4,50
Section width (mm)	360
Outer diameter of tyre [mm].	1116
Stat. radius (SLR) [mm]	495
Rolling circumference [mm].	3315
Tread depth (mm)	25,0
Number of lugs	20x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 A8	3150	40		4,50	
143 G	2725	90		4,50	