

## TYRES

|                 |              |
|-----------------|--------------|
| Product group   | Tyres        |
| Item number     | 15731140     |
| Valid tyre size | 14.5 - 20    |
| LI / SI / PR    | 139 D, 12 PR |
| TL/TT           | TL           |
| Brand           | BKT          |
| Tread pattern   | MP 570       |



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- The BKT MP 570 was developed for road construction and excavation work.
- The tyre features excellent traction and good self-cleaning properties.
- Designed for sandy, loose surfaces.

## Technical Informations

|                              |               |
|------------------------------|---------------|
| Item number                  | 15731140      |
| EAN                          | 8903094015252 |
| Valid tyre size              | 14.5 - 20     |
| LI / SI / PR                 | 139 D, 12 PR  |
| TL/TT                        | TL            |
| Brand                        | BKT           |
| Tread pattern                | MP 570        |
| Antistatic                   | No            |
| Tyre colour                  | Black         |
| ECE regulation number        | ECE 106       |
| Nettogewicht [kg] (gültig)   | 57,66         |
| Recommended rim size         | 11            |
| Permitted rim size           | 12SDC         |
| Maximum air pressure [bar].  | 3,00          |
| Section width (mm)           | 360           |
| Outer diameter of tyre [mm]. | 1116          |
| Stat. radius (SLR) [mm]      | 505           |
| Rolling circumference [mm].  | 3325          |
| Tread depth (mm)             | 25,0          |
| Number of lugs               | 22x2          |
| E-Ready                      | No            |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 139 D | 2430               | 65           |               | 3,00                     |              |