

## TYRES

Product group	Tyres
Item number	15731163
Valid tyre size	400 / 70 - 20
LI / SI / PR	152 A8, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	MP 600



Bohnenkamp  
Moving Professionals

**BKT**  
GROWING TOGETHER

## Notes and features

- The MP 600 is a versatile multi purpose tyre for various uses.
- It is suitable for operations with a large share of road journeys but also as an agro-industrial tyre, for example on skid steer loaders and telescopic handlers.
- The wide tread pattern provides for good traction on any surface and for an exceptional level of stability.
- The lug design features very good self-cleaning properties.
- Owing to its sturdy carcass, the tyre is characterised by a high level of durability and a long service life.

## Technical Informations

Item number	15731163
EAN	8903094048403
Valid tyre size	400 / 70 - 20
Alternative size 1	16.0/70-20
LI / SI / PR	152 A8, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	MP 600
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	69,13
Recommended rim size	13SDC
Permitted rim size	12
Maximum air pressure [bar].	4,00
Section width (mm)	405
Outer diameter of tyre [mm].	1085
Stat. radius (SLR) [mm]	494
Rolling circumference [mm].	3271
Tread depth (mm)	33,5
Number of lugs	17x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 A8	3550	40		4,00	