

## **TYRES**

Product group	Tyres	
Item number	15731170	
Valid tyre size	16.0 / 70 - 20	
LI / SI / PR	147 F, 16 PR	
TL/TT	тт	
Brand	ВКТ	
Tread pattern	MT 612	



## **Notes and features**

- Sturdy carcass for heavy-duty operations.
- Wide tread blocks for maximum traction.

• Extra-wide running tread for excellent flotation properties.



## **Technical Informations**

Item number	15731170
EAN	8903094035922
Valid tyre size	16.0 / 70 - 20
Alternative size 1	405/70-20
LI / SI / PR	147 F, 16 PR
TL/TT	тт
Brand	BKT
Tread pattern	MT 612
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	60,20
Recommended rim size	13.00T
Maximum air pressure [bar].	4,50
Section width (mm)	408
Outer diameter of tyre [mm].	1100
Stat. radius (SLR) [mm]	520
Rolling circumference [mm].	3327
Tread depth (mm)	18,0
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
147 F	3075	80		4,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.