

TYRES

Product group	Tyres	
Item number	15731230	
Valid tyre size	445 / 65 - 22.5	
LI / SI / PR	163 A8, 16 PR	
TL/TT	TL	
Brand	BKT	
Tread pattern	MP 590	



Notes and features

- The BKT MP 590 features a high level of stability and high load capacity owing to the tyre's width.
- The tyre is suitable to be used on a variety of utility vehicles and for various uses.



Technical Informations

Item number	15731230
item number	
EAN	8903094014729
Valid tyre size	445 / 65 - 22.5
Alternative size 1	18-22.5
LI / SI / PR	163 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	MP 590
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	91,95
Recommended rim size	14.0
Permitted rim size	14.00
Maximum air pressure [bar].	5,50
Section width (mm)	480
Outer diameter of tyre [mm].	1190
Stat. radius (SLR) [mm]	530
Rolling circumference [mm].	3534
Tread depth (mm)	31,0
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
163 A8	4875	40		5,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.