

TYRES

Product group	Tyres
Item number	15735201
Valid tyre size	315 / 55 R 16
LI / SI / PR	124 F / 120 K
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 540



Notes and features

- The BKT Multimax MP 540 was developed for multipurpose vehicles in municipality/maintenance applications.
- Thanks to its reinforced, steel belted nylon casing, the tyre provides high load capacity at high speeds.

Technical Informations

Item number	15735201
EAN	8903094068999
Valid tyre size	315 / 55 R 16
LI / SI / PR	124 F / 120 K
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 540
M+S	M+S
Carcass properties	POR
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	33,45
Recommended rim size	10.00
Permitted rim size	11
Maximum air pressure [bar].	6,50
Section width (mm)	305
Outer diameter of tyre [mm].	751
Stat. radius (SLR) [mm]	354
Rolling circumference [mm].	2325
Tread depth (mm)	17,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
124 F	1600	80		6,50	
120 K	1400	110		6,50	