

## TYRES

Product group	Tyres
Item number	15735210
Valid tyre size	425 / 55 R 17
LI / SI / PR	134 G
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 513



## Notes and features

- Radial MPT tyre for various uses such as on telescopic handlers, communal vehicles or working equipment.
- A reinforced bead and stiffening steel belts for high load capacity and protection from external impact.
- Tractor tread pattern for ideal traction and self-cleaning properties on soft and wet terrain.

## Technical Informations

Item number	15735210
EAN	8903094038411
Valid tyre size	425 / 55 R 17
LI / SI / PR	134 G
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 513
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	50,95
Recommended rim size	13
Permitted rim size	13.00
Maximum air pressure [bar].	3,50
Section width (mm)	421
Outer diameter of tyre [mm].	900
Stat. radius (SLR) [mm]	399
Rolling circumference [mm].	2695
Tread depth (mm)	28,0
Number of lugs	17x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
134 G	2120	90		3,50	