

TYRES

Product group	Tyres
Item number	15735216
Valid tyre size	280 / 80 R 18
LI / SI / PR	132 A8 / 132 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 522



Notes and features

- Agro-industrial / MPT tyres for telescopic handlers, wheel loaders and backhoe loaders.
- Radial carcass with reinforcing steel belt for high load capacity and protection against puncture damage.
- Aggressive tread lugs for traction under any working conditions.
- Special rubber compound for hard terrain.
- Deep tread depth for a long service life.

Technical Informations

Item number	15735216
EAN	8903094045044
Valid tyre size	280 / 80 R 18
Alternative size 1	10.5/80R18
LI / SI / PR	132 A8 / 132 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 522
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	42,42
Recommended rim size	9
Permitted rim size	W8, W9, W10
Maximum air pressure [bar].	4,00
Section width (mm)	282
Outer diameter of tyre [mm].	907
Stat. radius (SLR) [mm]	421
Rolling circumference [mm].	2748
Tread depth (mm)	33,5
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
132 A8	2000	40		4,00	
132 B	2000	50		4,00	