

TYRES

Product group	Tyres
Item number	15735217
Valid tyre size	340 / 80 R 18
LI / SI / PR	143 A8 / 143 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 522



Notes and features

- Agro-industrial / MPT tyres for telescopic handlers, wheel loaders and backhoe loaders.
- Radial carcass with reinforcing steel belt for high load capacity and protection against puncture damage.
- Aggressive tread lugs for traction under any working conditions.
- Special rubber compound for hard terrain.
- Deep tread depth for a long service life.

Technical Informations

Item number	15735217
EAN	8903094048793
Valid tyre size	340 / 80 R 18
Alternative size 1	12.5/80R18
LI / SI / PR	143 A8 / 143 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 522
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	57,64
Recommended rim size	W11
Permitted rim size	W10, 12, 11SDC, 12, 12SDC
Maximum air pressure [bar].	4,20
Section width (mm)	343
Outer diameter of tyre [mm].	1001
Stat. radius (SLR) [mm]	458
Rolling circumference [mm].	3023
Tread depth (mm)	34,0
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 A8	2725	40		4,20	
143 B	2725	50		4,20	