

TYRES

Product group	Tyres
Item number	15735218
Valid tyre size	380 / 75 R 20
LI / SI / PR	148 A8 / 148 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 522



Notes and features

- Agro-industrial / MPT tyres for telescopic handlers, wheel loaders and backhoe loaders.
- Radial carcass with reinforcing steel belt for high load capacity and protection against puncture damage.
- Aggressive tread lugs for traction under any working conditions.
- Special rubber compound for hard terrain.
- Deep tread depth for a long service life.

Technical Informations

Item number	15735218
EAN	8903094045877
Valid tyre size	380 / 75 R 20
Alternative size 1	14.5R20
LI / SI / PR	148 A8 / 148 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 522
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	72,20
Recommended rim size	W12
Permitted rim size	W11, 11, 12
Maximum air pressure [bar].	4,00
Section width (mm)	384
Outer diameter of tyre [mm].	1074
Stat. radius (SLR) [mm]	483
Rolling circumference [mm].	3251
Tread depth (mm)	37,5
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 A8	3150	40		4,00	
148 B	3150	50		4,00	