

TYRES

Product group	Tyres
Item number	15735220
Valid tyre size	400 / 70 R 20
LI / SI / PR	149 A8 / 149 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 522



Notes and features

- Agro-industrial / MPT tyres for telescopic handlers, wheel loaders and backhoe loaders.
- Radial carcass with reinforcing steel belt for high load capacity and protection against puncture damage.
- Aggressive tread lugs for traction under any working conditions.
- Special rubber compound for hard terrain.
- Deep tread depth for a long service life.

Technical Informations

Item number	15735220
EAN	8903094033829
Valid tyre size	400 / 70 R 20
Alternative size 1	16.0/70R20
LI / SI / PR	149 A8 / 149 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 522
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	74,65
Recommended rim size	13
Permitted rim size	12SDC, 13SDC, 14
Maximum air pressure [bar].	4,00
Section width (mm)	404
Outer diameter of tyre [mm].	1068
Stat. radius (SLR) [mm]	476
Rolling circumference [mm].	3222
Tread depth (mm)	38,5
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A8	3250	40		4,00	
149 B	3250	50		4,00	