

TYRES

Product group	Tyres
Item number	15735221
Valid tyre size	395 / 85 R 20
LI / SI / PR	168 J
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 33



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT Earthmax SR 33 is a radial MPT tyre
- The block pattern provides very good traction on soft, sandy or muddy ground
- The wide spaces between the tread pattern blocks enable very good self-cleaning
- The strong, all-steel casing ensures excellent cut resistance and a long service life

Technical Informations

Item number	15735221
EAN	8903094050611
Valid tyre size	395 / 85 R 20
LI / SI / PR	168 J
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 33
M+S	M+S
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	106,80
Recommended rim size	10.00W
Permitted rim size	10.00HF
Maximum air pressure [bar].	8,50
Section width (mm)	394
Outer diameter of tyre [mm].	1184
Stat. radius (SLR) [mm]	538
Rolling circumference [mm].	3589
Tread depth (mm)	25,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 J	5600	100		8,50	