

## **TYRES**

Product group	Tyres
Item number	15735222
Valid tyre size	335 / 80 R 20
LI / SI / PR	149 K
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 540



## **Notes and features**

- The BKT Multimax MP 540 was developed for multipurpose vehicles in municipality/maintenance applications.
- Thanks to its reinforced, steel belted nylon casing, the tyre provides high load capacity at high speeds.



## **Technical Informations**

Item number	15735222
EAN	8903094033539
Valid tyre size	335 / 80 R 20
LI / SI / PR	149 K
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 540
M+S	M+S
Carcass properties	POR
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	59,19
Recommended rim size	11
Maximum air pressure [bar].	6,50
Section width (mm)	340
Outer diameter of tyre [mm].	1044
Stat. radius (SLR) [mm]	492
Rolling circumference [mm].	3258
Tread depth (mm)	16,5
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 K	3250	110		6,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.