

TYRES

Product group	Tyres
Item number	15735226
Valid tyre size	365 / 70 R 18
LI / SI / PR	133 G
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 513



Notes and features

- Radial MPT tyre for various uses such as on telescopic handlers, communal vehicles or working equipment.
- A reinforced bead and stiffening steel belts for high load capacity and protection from external impact.
- Tractor tread pattern for ideal traction and self-cleaning properties on soft and wet terrain.

Technical Informations

Item number	15735226
EAN	8903094051366
Valid tyre size	365 / 70 R 18
LI / SI / PR	133 G
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 513
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	50,13
Recommended rim size	11
Permitted rim size	11SDC, 12, 12SDC
Maximum air pressure [bar].	3,75
Section width (mm)	360
Outer diameter of tyre [mm].	969
Stat. radius (SLR) [mm]	448
Rolling circumference [mm].	2954
Tread depth (mm)	28,5
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
133 G	2060	90		3,75	
	2370	40		3,75	