

TYRES

Product group	Tyres
Item number	15735227
Valid tyre size	14.00 R 20
LI / SI / PR	164 / 160 J (166 G), 22 PR
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 33



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT Earthmax SR 33 is a radial MPT tyre
- The block pattern provides very good traction on soft, sandy or muddy ground
- The wide spaces between the tread pattern blocks enable very good self-cleaning
- The strong, all-steel casing ensures excellent cut resistance and a long service life

Technical Informations

Item number	15735227
EAN	8903094057757
Valid tyre size	14.00 R 20
LI / SI / PR	164 / 160 J (166 G), 22 PR
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 33
M+S	M+S
Antistatic	No
Shore	62
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	108,88
Recommended rim size	10.0
Permitted rim size	9.0, 10.00W
Maximum air pressure [bar].	7,50
Section width (mm)	390
Outer diameter of tyre [mm].	1250
Stat. radius (SLR) [mm]	576
Rolling circumference [mm].	3840
Tread depth (mm)	23,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 J	5000	100		7,50	
166 G	5300	90		7,50	