

TYRES

Product group	Tyres
Item number	15735228
Valid tyre size	375 / 70 R 20
LI / SI / PR	136 G
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 513



Notes and features

- Radial MPT tyre for various uses such as on telescopic handlers, communal vehicles or working equipment.
- A reinforced bead and stiffening steel belts for high load capacity and protection from external impact.
- Tractor tread pattern for ideal traction and self-cleaning properties on soft and wet terrain.

Technical Informations

Item number	15735228
EAN	8903094051847
Valid tyre size	375 / 70 R 20
LI / SI / PR	136 G
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 513
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	62,23
Recommended rim size	12
Permitted rim size	W10, DW10, 11, 11SDC, W11, DW11, 12SDC
Maximum air pressure [bar].	3,50
Section width (mm)	377
Outer diameter of tyre [mm].	1034
Stat. radius (SLR) [mm]	472
Rolling circumference [mm].	3121
Tread depth (mm)	27,5
Number of lugs	19x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
136 G	2240	90		3,50	
	2580	40		3,50	