

TYRES

| | |
|-----------------|-----------------|
| Product group | Tyres |
| Item number | 15735230 |
| Valid tyre size | 405 / 70 R 20 |
| LI / SI / PR | 136 G |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Multimax MP 513 |



Notes and features

- Radial MPT tyre for various uses such as on telescopic handlers, communal vehicles or working equipment.
- A reinforced bead and stiffening steel belts for high load capacity and protection from external impact.
- Tractor tread pattern for ideal traction and self-cleaning properties on soft and wet terrain.

Technical Informations

| | |
|------------------------------|-----------------|
| Item number | 15735230 |
| EAN | 8903094038428 |
| Valid tyre size | 405 / 70 R 20 |
| LI / SI / PR | 136 G |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | Multimax MP 513 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54 |
| Nettogewicht [kg] (gültig) | 68,45 |
| Recommended rim size | 13 |
| Permitted rim size | 13SDC, 12SDC |
| Maximum air pressure [bar]. | 3,50 |
| Section width (mm) | 407 |
| Outer diameter of tyre [mm]. | 1076 |
| Stat. radius (SLR) [mm] | 493 |
| Rolling circumference [mm]. | 3253 |
| Tread depth (mm) | 29,0 |
| Number of lugs | 18x2 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 136 G | 2240 | 90 | | 3,50 | |