

TYRES

Product group	Tyres
Item number	15735231
Valid tyre size	405 / 70 R 20
LI / SI / PR	136 G
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 515



Notes and features

- The BKT MP515 is a radial tyre for manure spreaders and municipal tractors.
- Its agricultural tread pattern with balanced structure provides good self-cleaning and offers excellent ride comfort on the road.
- The strong nylon casing with steel belts and the solid rubber compound guarantee puncture resistance and a long service life.
- The tyre is approved for speeds up to 90 km/h.

Technical Informations

Item number	15735231
EAN	8903094056545
Valid tyre size	405 / 70 R 20
LI / SI / PR	136 G
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 515
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	69,99
Recommended rim size	13
Permitted rim size	13SDC, 12SDC, 11SDC, 11
Maximum air pressure [bar].	3,50
Section width (mm)	407
Outer diameter of tyre [mm].	1076
Stat. radius (SLR) [mm]	493
Rolling circumference [mm].	3286
Tread depth (mm)	28,0
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
136 G	2240	90		3,50	
	2580	40		3,50	