

## **TYRES**

Product group	Tyres
Item number	15735233
Valid tyre size	405 / 70 R 20
LI / SI / PR	155 A2 / 151 A4
TL/TT	TL
Brand	BKT
Tread pattern	BK Loader 53





## **Notes and features**

- The BK-Loader 53 is a tyre for loaders in industrial and heavy transport use, particularly recycling
- Its extremely deep tread pattern and rubber compound tailored to the application ensure slow tread wear e.g. on concrete slabs, and resistance to cuts and punctures
- Its specially designed aramid belt reliably protects the tyre against damages
- The special tread pattern design provides excellent lateral stability in harsh conditions
- Additionally, the tyre has excellent self-cleaning properties and good grip on wet and dry surfaces due to this tread pattern



## **Technical Informations**

Item number	15735233
EAN	8903094054428
Valid tyre size	405 / 70 R 20
LI / SI / PR	155 A2 / 151 A4
TL/TT	TL
Brand	BKT
Tread pattern	BK Loader 53
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	122,60
Recommended rim size	13
Permitted rim size	14, 13SDC, 12, 12SDC
Maximum air pressure [bar].	5,50
Section width (mm)	407
Outer diameter of tyre [mm].	1097
Stat. radius (SLR) [mm]	511
Speed Radius Index (SRI)	525
Rolling circumference [mm].	3339
Tread depth (mm)	56,5
Number of lugs	20x2
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 A2	3875	10		5,50	
151 A4	3450	20		5,50	