

TYRES

Product group	Tyres
Item number	15735235
Valid tyre size	425 / 75 R 20
LI / SI / PR	148 G
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 513



Notes and features

- Radial MPT tyre for various uses such as on telescopic handlers, communal vehicles or working equipment.
- A reinforced bead and stiffening steel belts for high load capacity and protection from external impact.
- Tractor tread pattern for ideal traction and self-cleaning properties on soft and wet terrain.

Technical Informations

Item number	15735235
EAN	8903094034703
Valid tyre size	425 / 75 R 20
LI / SI / PR	148 G
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 513
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	77,85
Recommended rim size	13
Permitted rim size	13SDC, 11SDC, 12SDC, 11, 12
Maximum air pressure [bar].	4,00
Section width (mm)	421
Outer diameter of tyre [mm].	1146
Stat. radius (SLR) [mm]	521
Rolling circumference [mm].	3479
Tread depth (mm)	30,0
Number of lugs	21x2
Lug width (mm)	48
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 G	3150	90		4,00	