

TYRES

Product group	Tyres
Item number	15735237
Valid tyre size	400 / 80 R 24
LI / SI / PR	162 A8 / 162 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 522



Notes and features

- Agro-industrial / MPT tyres for telescopic handlers, wheel loaders and backhoe loaders.
- Radial carcass with reinforcing steel belt for high load capacity and protection against puncture damage.
- Aggressive tread lugs for traction under any working conditions.
- Special rubber compound for hard terrain.
- Deep tread depth for a long service life.

Technical Informations

Item number	15735237
EAN	8903094051397
Valid tyre size	400 / 80 R 24
LI / SI / PR	162 A8 / 162 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 522
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	88,42
Recommended rim size	DW13
Permitted rim size	DW12, DW13L, DW14L
Maximum air pressure [bar].	5,00
Section width (mm)	404
Outer diameter of tyre [mm].	1250
Stat. radius (SLR) [mm]	553
Rolling circumference [mm].	3778
Tread depth (mm)	37,5
Number of lugs	21x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 A8	4750	50		5,00	
162 B	4750	40		5,00	