

## TYRES

Product group	Tyres
Item number	15735240
Valid tyre size	460 / 70 R 24
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 522



## Notes and features

- Agro-industrial / MPT tyres for telescopic handlers, wheel loaders and backhoe loaders.
- Radial carcass with reinforcing steel belt for high load capacity and protection against puncture damage.
- Aggressive tread lugs for traction under any working conditions.
- Special rubber compound for hard terrain.
- Deep tread depth for a long service life.

## Technical Informations

Item number	15735240
EAN	8903094031313
Valid tyre size	460 / 70 R 24
Alternative size 1	17.5LR24
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 522
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	101,62
Recommended rim size	DW15L
Permitted rim size	DW14L, DW16L
Maximum air pressure [bar].	4,00
Section width (mm)	465
Outer diameter of tyre [mm].	1250
Stat. radius (SLR) [mm]	568
Rolling circumference [mm].	3766
Tread depth (mm)	39,5
Number of lugs	18x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 A8	4375	40		4,00	
159 B	4375	50		4,00	