

TYRES

Product group	Tyres
Item number	15735241
Valid tyre size	400 / 80 R 24
LI / SI / PR	162 A8 / 162 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 527



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The MP 527 is a radial multi purpose tyre for telescopic handlers.
- The reinforced side walls provide outstanding stability during lifting.
- The cut resistant rubber compound and sturdy carcass protect the tyre from puncture damage and allow for a long service life.

Technical Informations

Item number	15735241
EAN	8903094052226
Valid tyre size	400 / 80 R 24
LI / SI / PR	162 A8 / 162 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 527
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	99,40
Recommended rim size	DW13
Permitted rim size	DW12, DW13L, DW14L
Maximum air pressure [bar].	5,00
Section width (mm)	404
Outer diameter of tyre [mm].	1250
Stat. radius (SLR) [mm]	578
Speed Radius Index (SRI)	600
Rolling circumference [mm].	3834
Tread depth (mm)	32,5
Number of lugs	29x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 A8	4750	50		5,00	
162 B	4750	40		5,00	