

TYRES

Product group	Tyres
Item number	15735243
Valid tyre size	400 / 70 R 24
LI / SI / PR	152 A8 / 152 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 527



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The MP 527 is a radial multi purpose tyre for telescopic handlers.
- The reinforced side walls provide outstanding stability during lifting.
- The cut resistant rubber compound and sturdy carcass protect the tyre from puncture damage and allow for a long service life.

Technical Informations

Item number	15735243
EAN	8903094053483
Valid tyre size	400 / 70 R 24
LI / SI / PR	152 A8 / 152 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 527
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	87,00
Recommended rim size	13
Permitted rim size	DW12, DW13L, DW13, 13SDC, DW14L
Maximum air pressure [bar].	4,00
Section width (mm)	404
Outer diameter of tyre [mm].	1170
Stat. radius (SLR) [mm]	542
Speed Radius Index (SRI)	575
Rolling circumference [mm].	3597
Tread depth (mm)	28,5
Number of lugs	27x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 A8	3550	40		4,00	
152 B	3550	50		4,00	