

TYRES

Product group	Tyres
Item number	15735245
Valid tyre size	495 / 70 R 24
LI / SI / PR	155 G
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 513



Notes and features

- Radial MPT tyre for various uses such as on telescopic handlers, communal vehicles or working equipment.
- A reinforced bead and stiffening steel belts for high load capacity and protection from external impact.
- Tractor tread pattern for ideal traction and self-cleaning properties on soft and wet terrain.

Technical Informations

Item number	15735245
EAN	8903094035908
Valid tyre size	495 / 70 R 24
LI / SI / PR	155 G
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 513
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	107,56
Recommended rim size	W16L
Permitted rim size	DW15L, DW16L, W15L
Maximum air pressure [bar].	3,50
Section width (mm)	499
Outer diameter of tyre [mm].	1304
Stat. radius (SLR) [mm]	588
Rolling circumference [mm].	3974
Tread depth (mm)	35,0
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 G	3875	90		3,50	