

TYRES

Product group	Tyres
Item number	15735252
Valid tyre size	500 / 70 R 24
LI / SI / PR	164 A8 / 164 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 527



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The MP 527 is a radial multi purpose tyre for telescopic handlers.
- The reinforced side walls provide outstanding stability during lifting.
- The cut resistant rubber compound and sturdy carcass protect the tyre from puncture damage and allow for a long service life.

Technical Informations

Item number	15735252
EAN	8903094052233
Valid tyre size	500 / 70 R 24
Alternative size 1	19.5LR24
LI / SI / PR	164 A8 / 164 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 527
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	133,90
Recommended rim size	DW16L
Permitted rim size	DW15L, DW18L
Maximum air pressure [bar].	4,00
Section width (mm)	503
Outer diameter of tyre [mm].	1310
Stat. radius (SLR) [mm]	597
Speed Radius Index (SRI)	625
Rolling circumference [mm].	4019
Tread depth (mm)	34,5
Number of lugs	25x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 A8	5000	40		4,00	
164 B	5000	50		4,00	